



JC400

Dual-Channel Dashcam

JC400 4G dashcam can significantly increase the safety, efficiency, and sustainability of operations that power the fleet. Using the driver's behavior analysis of the driving recorder and G-sensor-induced collision technology. It helps you clarify what happens in case of an accident, resolve disputes related to road incidents and coach your drivers towards better driving.





Various Communication Standards

It is able to communicate via 2G/3G/4G and WiFi.



Dual Channel Recording

The integrated road-facing camera and the remote cabin-view camera for monitoring what's happening inside or the waterproof camera that can be mounted on the side mirror/trunk/trailer/dump body for your specific business needs.



Real-Time Tracking

The video recorder can be used as a tracker to locate the vehicle and collect and upload data such as speed and time in real-time.



Event Video to Cloud

Videos triggered by a collision, vibrating, SOS call, and other exceptions will be auto uploaded to the cloud.



Driving Behavior Analysis (DBA)

The dashcam can detect the driver's dangerous driving practices such as harsh acceleration, harsh braking, etc.



Panic Button

This enables the driver to call for help in emergencies.







Specification

Network

WiFi	2.4GHz, 802.11 b/g/n
ВТ	BLE 4.0
Eurasian Version	GSM: 850/900/1800/1900MHz WCDMA: B1/B2/B5/B8 FDD LTE: B1/B3/B5/B7/B8/B19/B20 TDD LTE: B38/B39/B40/B41 (100M)
American Version	GSM: 850/1800/1900MHz WCDMA: B2/B4/B5 FDD LTE: B2/B3/B4/B5/B7/B12/B17 TDD LTE: B38/B41 (100M)

Configuration

ONL	0.554 5.555 1.4045 450
CPU	Quad-core 1.4GHz A53
Operating System	Android 8.1 GO
GNSS	GPS+BDS
Sensor	6-axis
Mic	\checkmark
Speaker	\checkmark
Data Interface	Micro USB 2.0
Memory	TF card (Max. 256GB)
SIM Card	Nano
LED	Red (Power), Blue (Cellular), Green (GNSS)

Camera

Main Unit	Front camera: 1920×1080/25FPS/F2.2/full color
Subcamera (Optional)	Remote cabin-view camera: 1280x720/15FPS/F2.0/full color in daytime & monochrome in dim light IP67 waterproof camera: 1280x720/full color around the clock
Image Format	H.264

Others

Battery	External: 450mAh
Power Supply	Power cable: B+/ACC/GND
Operating Temperature	-20°C to +65°C
Operating Voltage	9–30V DC
Device Weight	233g
Device Dimension	109x69x52mm
Certifications	FCC/CE/RoH\$